

## WELDSTATION™ DUAL

The Premier Fume Extraction Solution for Hundreds of Trade Schools and Welding Labs

### Standard Features

- **Hands-free Fume Extraction**
- **Self-Contained** for Reduced Project Cost
- **Plug-and-Play Functionality** for Easy Installation
- **Dual 5' x 5' Table Design** with Adjustable Shelf
- **Side-by-Side or Back-to-Back Configuration**
- **VFD Standard** for Increased Energy Savings, Noise Reduction, and Motor Speed Control
- **Automatic On / Off Functionality**
- **Built-In Two-Stage Spark Arrestors** and **Standard** with Fire Retardant Filters
- **Optional Weld Curtain Available**

### Specifications

**Air Flow:** 4,000 CFM (2,000 CFM per Booth)

**Filter Cartridges:** Qty (4) Fire Retardant Filters with 226sf of Media (€34sf total) – Available in High Efficiency Nanofiber

**Spark Arrestors:** Qty (2) 24" x 24" x 2" Metal Spark Baffle plates and (2) 24" x 24" x 2" Metal Mesh Filters

**Motor / Blower:** 5HP, Direct Drive, Backward Inclined Blower

**Power:** Three Phase – 208, 240, or 460 Volt, 6A – 19A

**Pulse Valves:** Qty (2) 1" Pulsing Valves – auto or manual

**Compressed Air:** 1" NPT Compressed Air connection – 70–90 PSI required

**Silencing:** 65 – 74 dBA at 5'

**Dimensions:** 116" L x 41" D x 124" H

**Weight:** 2,100 lbs – 12-Gauge Solid Weld Construction

